

1. Explain the test on fresh concrete.(MAY 2019)(MAY 2016)(NOV 2019)(NOV 2017)(NOV 2016)

The following tests are commonly employed to measure workability.

- (a) Slump Test
- (b) Compacting Factor Test
- (c) Flow Test
- (d) Kelly Ball Test
- (e) Vee Bee Consistometer Test.

Slump Test

Slump test is the most commonly used method of measuring consistency of concrete which can be employed either in laboratory or at site of work. It is not a suitable method for very wet or very dry concrete. It does not measure all factors contributing to workability, nor is it always representative of the placability of the concrete. However, it is used conveniently as a control test and gives an indication of the uniformity of concrete from batch to batch. Repeated batches of the same mix, brought to the same slump, will have the same water content and water cement ratio, provided the weights of aggregate, cement and admixtures are uniform and aggregate grading is within acceptable limits. Additional information on workability and quality of concrete can be obtained by observing the manner in which concrete slumps. Quality of concrete can also be further assessed by giving a few tappings or blows by tamping rod to the base plate. The deformation shows the characteristics of concrete with respect to tendency for segregation.

The apparatus for conducting the slump test essentially consists of a metallic mould in the form of a frustum of a cone having the internal dimensions as under:

Bottom diameter	20 cm
Top diameter	10 cm
Height	30 cm

The thickness of the metallic sheet for the mould should not be thinner than 1.6 mm. Sometimes the mould is provided with suitable guides for lifting vertically up. For tamping the concrete, a steel tamping rod 16 mm dia, 0.6 meter long with bullet end is used. Fig. 6.1, shows the details of the slump cone apparatus. The internal surface of the mould is

thoroughly cleaned and freed from superfluous moisture and adherence of any old set concrete before commencing the test. The mould is placed on a smooth, horizontal, rigid and non-absorbant surface. The mould is then filled in four layers, each approximately 1/4 of the height of the mould. Each layer is tamped 25 times by the tamping rod taking care to distribute the strokes evenly over the cross section. After the top layer has been rodded, the concrete is struck off level with a trowel and tamping rod. The mould is removed from the concrete immediately by raising it slowly and carefully in a vertical direction. This allows the concrete to subside. This subsidence is referred as SLUMP of concrete. The difference in level between the height of the mould and that of the highest point of the subsided concrete is measured. This difference in height in mm. is taken as Slump of Concrete. ASTM measure the centre of the slumped concrete as the difference in height. ASTM also specifies 3 layers.

It indicates the characteristic of concrete in addition to the slump value. If the concrete slumps evenly it is called true slump. If one half of the cone slides down, it is called shear slump. In case of a shear slump, the slump value is measured as the difference in height between the height of the mould and the average value of the subsidence. Shear slump also indicates that the concrete is non-cohesive and shows the characteristic of segregation.

It is seen that the slump test gives fairly good consistent results for a plastic-mix. This test is not sensitive for a stiff-mix. In case of dry-mix, no variation can be detected between mixes of different workability. In the case of rich mixes, the value is often satisfactory, their slump being sensitive to variations in workability. IS 456 of 2000 suggests that in the “very low” category of workability where strict control is necessary, for example, pavement quality concrete, (PQC) measurement of workability by determination of compacting factor will be more appropriate than slump and a value of 0.75 to 0.80 compacting factor is suggested.

The above IS also suggests that in the “very high” category of workability, measurement of workability by determination of “flow” by flow test will be more appropriate. However, in a lean-mix with a tendency of harshness a true slump can easily change to shear slump. In such case, the tests should be repeated.

Despite many limitations, the slump test is very useful on site to check day-to-day or hour-to-hour variation in the quality of mix. An increase in slump, may mean for instance that the moisture content of the aggregate has suddenly increased or there has been sudden change in the grading of aggregate. The slump

test gives warning to correct the causes for change of slump value. The simplicity of this test is yet another reason, why this test is still popular in spite of the fact that many other workability tests are in vogue. Table 6.1 shows the nominal slump value for different degrees of workability.

The Bureau of Indian standards, in the past, generally adopted compacting factor test values for denoting workability. Even in the IS 10262 of 1982 dealing with Recommended Guide Line for Concrete Mix Design, adopted compacting factor for denoting workability. But now in the revision of IS 456 of 2000 the code has reverted back to slump value to denote the workability rather than compacting factor. It shows that slump test has more practical utility than the other tests for workability.

Compacting Factor Test

The compacting factor test is designed primarily for use in the laboratory but it can also be used in the field. It is more precise and sensitive than the slump test and is particularly useful for concrete mixes of very low workability as are normally used when concrete is to be compacted by vibration. Such dry concrete are insensitive to slump test.

The compacting factor test has been developed at the Road Research Laboratory U.K. and it is claimed that it is one of the most efficient tests for measuring the workability of concrete. This test works on the principle of determining the degree of compaction achieved by a standard amount of work done by allowing the concrete to fall through a standard height. The degree of compaction, called the compacting factor is measured by the density ratio i.e., the ratio of the density actually achieved in the test to density of same concrete fully compacted.

The sample of concrete to be tested is placed in the upper hopper up to the brim. The trap-door is opened so that the concrete falls into the lower hopper. Then the trap-door of the lower hopper is opened and the concrete is allowed to fall into the cylinder. In the case of a dry-mix, it is likely that the concrete may not fall on opening the trap-door. In such a case, a slight poking by a rod may be required to set the concrete in motion. The excess concrete remaining above the top level of the cylinder is then cut off with the help of plane blades supplied with the apparatus. The outside of the cylinder is wiped clean. The concrete is filled up exactly upto the top level of the cylinder. It is weighed to the nearest 10 grams.

This weight is known as “Weight of partially compacted concrete”. The cylinder is emptied and then refilled with the concrete from the same sample in layers approximately 5 cm deep. The layers are heavily rammed or preferably vibrated so as to obtain full compaction. The top surface of the fully compacted concrete is then carefully struck off level with the top of the cylinder and weighed to the nearest 10 gm. This weight is known as “Weight of fully compacted concrete

The weight of fully compacted concrete can also be calculated by knowing the proportion of materials, their respective specific gravities, and the volume of the cylinder. It is seen from experience, that it makes very little difference in compacting factor value, whether the weight of fully compacted concrete is calculated theoretically or found out actually after 100 per cent compaction.

It can be realised that the compacting factor test measures the inherent characteristics of the concrete which relates very close to the workability requirements of concrete and as such it is one of the good tests to depict the workability of concrete.

Vee Bee Consistometer Test

This is a good laboratory test to measure indirectly the workability of concrete. This test consists of a vibrating table, a metal pot, a sheet metal cone, a standard iron rod.

Slump test as described earlier is performed, placing the slump cone inside the sheet metal cylindrical pot of the consistometer. The glass disc attached to the swivel arm is turned and placed on the top of the concrete in the pot. The electrical vibrator is then switched on and simultaneously a stop watch started. The vibration is continued till such a time as the conical shape of the concrete disappears and the concrete assumes a cylindrical shape. This can be judged by observing the glass disc from the top for disappearance of transparency. Immediately when the concrete fully assumes a cylindrical shape, the stop watch is switched off. The time required for the shape of concrete to change from slump cone shape to cylindrical shape in seconds is known as Vee Bee Degree. This method is very suitable for very dry concrete whose slump value cannot be measured by Slump Test, but the vibration is too vigorous for concrete with a slump greater than about 50 mm.

2.Explain the properties of hardened concrete and its compression , tension and flexural tests(MAY 2019)(MAY 2018)(MAY 2017)(MAY 2016)(NOV 2017)

Following are the properties of hardened concrete:

1. Strength of concrete
2. Concrete Creep
3. Shrinkage
4. Modulus Of Elasticity
5. Water tightness (impermeability)
6. Rate of Strength gain of Concrete

Strength:

The strength of concrete is basically referred to compressive strength and it depends upon three factors.

- 1- Paste Strength
- 2- Interfacial Bonding
- 3- Aggregate Strength

Paste strength:

It is mainly due to the binding properties of cement that the ingredients are compacted together. If the paste has higher binding strength, higher will be strength of concrete.

Interfacial bonding:

Interfacial bonding is very necessary regarding the strength. Clay hampers the bonding between paste and aggregate. The aggregate should be washed for a better bonding between paste and aggregate.

Aggregate strength: It is mainly the aggregate that provide strength to concrete especially coarse aggregates which act just like bones in the body. Rough and angular aggregate provides better bonding and high strength.

Factors affecting Strength of concrete:

Following are the factors that affect the strength of concrete:

1. Water-Cement ratio
 2. Type of cementing material
 3. Amount of cementing material
 4. Type of aggregate
 5. Air content
 6. Admixtures
1. Water-Cement ratio:

It is water cement ratio that basically governs the property of strength. Lesser the water cement ratio, greater will be strength.

2. Type of cement:

Type of cement affect the hydration process and therefore strength of concrete. Amount of cementing material: it is the paste that holds or binds all the ingredients. Thus greater amount of cementing material greater will be strength.

3. Type of Aggregate:

Rough and angular aggregates is preferable as they provide greater bonding.

4. Admixtures:

Chemical admixtures like plasticizers reduce the water cement ratio and increase the strength of concrete at same water cement ratio. Mineral admixtures affect the strength at later stage and increase the strength by increasing the amount of cementing material.

Creep in Concrete

Concrete creep is defined as: deformation of structure under sustained load. Basically, long term pressure or stress on concrete can make it change shape. This deformation usually occurs in the direction the force is being applied. Like a concrete column getting more compressed, or a beam bending. Creep does not necessarily cause concrete to fail or break apart. Creep is factored in when concrete structures are designed.

Shrinkage

Concrete is subjected to changes in volume either autogenous or induced. Volume change is one of the most detrimental properties of concrete, which affects the long-term strength and durability. To the practical engineer, the aspect of volume change in concrete is important from the point of view that it causes unsightly cracks in concrete.

Modulus of Elasticity

Young's modulus (E) describes tensile elasticity, or the tendency of an object to deform along an axis when opposing forces are applied along that axis; it is defined as the ratio of tensile stress to tensile strain. It is often referred to simply as the elastic modulus.

The modulus of elasticity of concrete is a function of the modulus of elasticity of the aggregates and the cement matrix and their relative proportions. The modulus of elasticity of concrete is relatively constant at low stress levels but starts decreasing at higher stress levels as matrix cracking develops. The elastic modulus of the hardened paste may be in the order of 10-30 GPa and aggregates about 45 to 85 GPa. The concrete composite is then in the range of 30 to 50 GPa.

Water Tightness

Watertightness is the ability of concrete to keep water out or in. Watertight is a versatile range of specialized ready mix concretes designed to protect a structure from water ingress or to retain water within a structure.

Water-tight concrete, or concrete made water-tight by some kind of waterproof coating, is frequently required, either for inclosing a space which must be kept dry, or for storing water or other liquids. Concrete, even when most carefully prepared from materials of the highest grade, is never of itself completely waterproof.

Rate of Strength Gain of Concrete

Strength can be defined as ability to resist change. One of the most valuable properties of the concrete is its strength. Strength is most important parameter that gives the picture of overall quality of concrete. Strength of concrete usually directly related to cement paste.

The Flexural Strength of Concrete

Concrete as we know is relatively strong in compression and weak in tension. In reinforced concrete members, little dependence is placed on the tensile strength of concrete since steel reinforcing bars are provided to resist all tensile forces.

However, tensile stresses are likely to develop in concrete due to drying shrinkage, rusting of steel reinforcement, temperature gradients and many other reasons. Therefore, the knowledge of tensile strength of concrete is of importance. A concrete road slab is called upon to resist tensile stresses from two principal sources— wheel loads and volume change in the concrete. Wheel loads may cause high tensile stresses. due to bending, when there is an inadequate subgrade support. Volume changes, resulting from changes in temperature and moisture, may produce tensile stresses, due to warping and due to the movement of the slab along the subgrade.

Stresses due to volume changes alone may be high. The longitudinal tensile stress in the bottom of the pavement, caused by restraint and temperature warping, frequently amounts to as much as 2.5 MPa at certain periods of the year and the corresponding stress in the transverse direction is approximately 0.9 MPa. These stresses are additive to those produced by wheel loads on unsupported portions of the slab.

Compression Test

Compression test is the most common test conducted on hardened concrete, partly because it is an easy test to perform, and partly because most of the desirable characteristic properties of concrete are qualitatively related to its compressive strength.

The compression test is carried out on specimens cubical or cylindrical in shape. Prism is also sometimes used, but it is not common in our country. Sometimes, the compression strength of concrete is determined using parts of a beam tested in flexure. The end parts of beam are left intact after failure in flexure and, because the beam is usually of square cross section, this part of the beam could be used to find out the compressive strength.

The cube specimen is of the size 15 x 15 x 15 cm. If the largest nominal size of the aggregate does not exceed 20 mm, 10 cm size cubes may also be used as an alternative. Cylindrical test specimens have a length equal to twice the diameter. They are 15 cm in diameter and 30 cm long. Smaller test specimens may be used but a ratio of the diameter of the specimen to maximum size of aggregate, not less than 3 to 1 is maintained.

Determination of Tensile Strength

Direct measurement of tensile strength of concrete is difficult. Neither specimens nor testing apparatus have been designed which assure uniform distribution of the “pull” applied to the concrete. While a number of investigations involving the direct measurement of tensile strength have been made, beam tests are found to be dependable to measure flexural strength property of concrete. The value of the modulus of rupture (extreme fibre stress in bending) depends on the dimension of the beam and manner of loading. The systems of loading used in finding out the flexural tension are central point loading and third point loading. In the central point loading, maximum fibre stress will come below the point of loading where the bending moment is maximum. In case of symmetrical two point loading, the critical crack may appear at any section, not strong enough to resist the stress within the middle third, where the bending moment is maximum. It can be expected that the two point loading will yield a lower value of the modulus of rupture than the centre point loading.

3. Explain the properties of fresh concrete – segregation and bleeding (MAY 2018)(NOV 2017)

Segregation

Segregation can be defined as the separation of the constituent materials of concrete. A good concrete is one in which all the ingredients are properly distributed to make a homogeneous mixture. If a sample of concrete exhibits a tendency for separation of say, coarse aggregate from the rest of the ingredients,

then, that sample is said to be showing the tendency for segregation. Such concrete is not only going to be weak; lack of homogeneity is also going to induce all undesirable properties in the hardened concrete.

There are considerable differences in the sizes and specific gravities of the constituent ingredients of concrete. Therefore, it is natural that the materials show a tendency to fall apart. Segregation may be of three types firstly, the coarse aggregate separating out or settling down from the rest of the matrix, secondly, the paste or matrix separating away from coarse aggregate and thirdly, water separating out from the rest of the material being a material of lowest specific gravity.

A well made concrete, taking into consideration various parameters such as grading, size, shape and surface texture of aggregate with optimum quantity of waters makes a cohesive mix. Such concrete will not exhibit any tendency for segregation. The cohesive and fatty characteristics of matrix do not allow the aggregate to fall apart, at the same time, the matrix itself is sufficiently contained by the aggregate. Similarly, water also does not find it easy to move out freely from the rest of the ingredients.

The conditions favourable for segregation are, as can be seen from the above para, the badly proportioned mix where sufficient matrix is not there to bind and contain the aggregates. Insufficiently mixed concrete with excess water content shows a higher tendency for segregation. Dropping of concrete from heights as in the case of placing concrete in column concreting will result in segregation. When concrete is discharged from a badly designed mixer, or from a mixer with worn out blades, concrete shows a tendency for segregation. Conveyance of concrete by conveyor belts, wheel barrow, long distance haul by dumper, long lift by skip and hoist are the other situations promoting segregation of concrete.

Vibration of concrete is one of the important methods of compaction. It should be remembered that only comparatively dry mix should be vibrated. If too wet a mix is excessively vibrated, it is likely that the concrete gets segregated. It should also be remembered that vibration is continued just for required time for optimum results. If the vibration is continued for a long time, particularly, in too wet a mix, it is likely to result in segregation of concrete due to settlement of coarse aggregate in matrix.

In the recent time we use concrete with very high slump particularly in RMC. The slump value required at the batching point may be in the order of 150 mm and at the pumping point the slump may be around 100 mm. At both these points cubes are cast. One has to take care to compact the cube mould with these high slump concrete. If sufficient care and understanding of concrete is not exercised, the concrete in the cube mould may get segregated and show low strength. Similarly care must be taken in the compaction of such concrete in actual structures to avoid segregation.

While finishing concrete floors or pavement, with a view to achieve a smooth surface, masons are likely to work too much with the trowel, float or tamping rule immediately on placing concrete. This immediate working on the concrete on placing, without any time interval, is likely to press the coarse aggregate down, which results in the movement of excess of matrix or paste to the surface. Segregation caused on this account, impairs the homogeneity and serviceability of concrete. The excess mortar at the top causes plastic shrinkage cracks.

It can be gathered that the tendency for segregation can be remedied by correctly proportioning the mix, by proper handling, transporting, placing, compacting and finishing. At any stage, if segregation is observed, remixing for a short time would make the concrete again homogeneous. As mentioned earlier, a cohesive mix would reduce the tendency for segregation. For this reason, use of certain workability agents and pozzolanic materials greatly help in reducing segregation. The use of air-entraining agent appreciably reduces segregation.

Segregation is difficult to measure quantitatively, but it can be easily observed at the time of concreting operation. The pattern of subsidence of concrete in slump test or the pattern of spread in the flow test gives a fair idea of the quality of concrete with respect to segregation.

Bleeding

Bleeding is sometimes referred as water gain. It is a particular form of segregation, in which some of the water from the concrete comes out to the surface of the concrete, being of the lowest specific gravity among all the ingredients of concrete. Bleeding is predominantly observed in a highly wet mix, badly proportioned and insufficiently mixed concrete. In thin members like roof slab or road slabs and when concrete is placed in sunny weather show excessive bleeding.

Due to bleeding, water comes up and accumulates at the surface. Sometimes, along with this water, certain quantity of cement also comes to the surface. When the surface is worked up with the trowel and floats, the aggregate goes down and the cement and water come up to the top surface. This formation of cement paste at the surface is known as “Laitance”.

In such a case, the top surface of slabs and pavements will not have good wearing quality. This laitance formed on roads produces dust in summer and mud in rainy season. Owing to the fact that the top surface has a higher content of water and is also devoid of aggregate matter; it also develops higher shrinkage cracks. If laitance is formed on a particular lift, a plane of weakness would form and the bond with the next lift would be poor. This could be avoided by removing the laitance fully before the next lift is poured.

Water while traversing from bottom to top, makes continuous channels. If the water cement ratio used is more than 0.7, the bleeding channels will remain continuous and unsegmented by the development of gel. This continuous bleeding channels are often responsible for causing permeability of the concrete structures.

While the mixing water is in the process of coming up, it may be intercepted by aggregates. The bleeding water is likely to accumulate below the aggregate. This accumulation of water creates water voids and reduces the bond between the aggregates and the paste. The above aspect is more pronounced in the case of flaky aggregate. Similarly, the water that accumulates below the reinforcing bars, particularly below the cranked bars, reduces the bond between the reinforcement and the concrete. The poor bond between the aggregate and the paste or the reinforcement and the paste due to bleeding can be remedied by revibration of concrete. The formation of laitance and the consequent bad effect can be reduced by delayed finishing operations.

Bleeding rate increases with time up to about one hour or so and thereafter the rate decreases but continues more or less till the final setting time of cement.

Bleeding is an inherent phenomenon in concrete. All the same, it can be reduced by proper proportioning and uniform and complete mixing. Use of finely divided pozzolanic materials reduces bleeding by creating a longer path for the water to traverse. It has been already discussed that the use of air-entraining agent is very effective in reducing the bleeding. It is also reported that the bleeding can

be reduced by the use of finer cement or cement with low alkali content. Rich mixes are less susceptible to bleeding than lean mixes.

The bleeding is not completely harmful if the rate of evaporation of water from the surface is equal to the rate of bleeding. Removal of water, after it had played its role in providing workability, from the body of concrete by way of bleeding will do good to the concrete. Early bleeding when the concrete mass is fully plastic, may not cause much harm, because concrete being in a fully plastic condition at that stage, will get subsided and compacted. It is the delayed bleeding, when the concrete has lost its plasticity, that causes undue harm to the concrete. Controlled revibration may be adopted to overcome the bad effect of bleeding.

Bleeding presents a very serious problem when Slip Form Paver is used for construction of concrete pavements. If too much of bleeding water accumulates on the surface of pavement slab, the bleeding water flows out over the unsupported sides which causes collapsing of sides. Bleeding becomes a major consideration in such situations.

In the pavement construction finishing is done by texturing or brooming. Bleeding water delays the texturing and application of curing compounds.

Method of Test for Bleeding of Concrete

This method covers determination of relative quantity of mixing water that will bleed from a sample of freshly mixed concrete.

A cylindrical container of approximately 0.01 m³ capacity, having an inside diameter of 250 mm and inside height of 280 mm is used. A tamping bar similar to the one used for slump test is used. A pipette for drawing off free water from the surface, a graduated jar of 100 cm³ capacity is required for test.

A sample of freshly mixed concrete is obtained. The concrete is filled in 50 mm layer for a depth of 250 ± 3 mm (5 layers) and each layer is tamped by giving strokes, and the top surface is made smooth by trowelling.

The test specimen is weighed and the weight of the concrete is noted. Knowing the total water content in 1 m³ of concrete quantity of water in the cylindrical container is also calculated.

The cylindrical container is kept in a level surface free from vibration at a temperature of $27^{\circ}\text{C} \pm 2^{\circ}\text{C}$. It is covered with a lid. Water accumulated at the top is drawn by means of pipette at 10 minutes interval for the first 40 minutes and at 30 minutes interval subsequently till bleeding ceases. To facilitate collection of bleeding water the container may be slightly tilted. All the bleeding water collected in a jar.

4. What are the factors influencing the strength of concrete? (May 2017)(NOV 2016)

Concrete strength is effected by many factors, such as

- quality of raw materials
- water/cement ratio
- coarse/fine aggregate ratio
- age of concrete
- compaction of concrete
- temperature
- relative humidity and
- curing of concrete.

Quality of Raw Materials:


Cement: Provided the cement conforms with the appropriate standard and it has been stored correctly (i.e. in dry conditions), it should be suitable for use in concrete.

Aggregates: Quality of aggregates, its size, shape, texture, strength etc determines the strength of concrete. The presence of salts (chlorides and sulphates), silt and clay also reduces the strength of concrete.

Water: frequently the quality of the water is covered by a clause stating “..the water should be fit for drinking..”. This criterion though is not absolute and reference should be made to respective codes for testing of water construction purpose.

Water / Cement Ratio:

The relation between water cement ratio and strength of concrete is shown in the plot as shown below:



The higher the water/cement ratio, the greater the initial spacing between the cement grains and the greater the volume of residual voids not filled by hydration products.

There is one thing missing on the graph. For a given cement content, the workability of the concrete is reduced if the water/cement ratio is reduced. A lower water cement ratio means less water, or more cement and lower workability.

However if the workability becomes too low the concrete becomes difficult to compact and the strength reduces. For a given set of materials and environment conditions, the strength at any age depends only on the water-cement ratio, providing full compaction can be achieved.

Coarse / fine aggregate ratio:

Following points should be noted for coarse/fine aggregate ratio:


- If the proportion of fines is increased in relation to the coarse aggregate, the overall aggregate surface area will increase.
- If the surface area of the aggregate has increased, the water demand will also increase.
- Assuming the water demand has increased, the water cement ratio will increase.
- Since the water cement ratio has increased, the compressive strength will decrease.

Aggregate / Cement Ratio:

Following points must be noted for aggregate cement ratio:

- If the volume remains the same and the proportion of cement in relation to that of sand is increased the surface area of the solid will increase.
- If the surface area of the solids has increased, the water demand will stay the same for the constant workability.
- Assuming an increase in cement content for no increase in water demand, the water cement ratio will decrease.
- If the water cement ratio reduces, the strength of the concrete will increase.

The influence of cement content on workability and strength is an important one to remember and can be summarized as follows:



1. For a given workability an increase in the proportion of cement in a mix has little effect on the water demand and results in a reduction in the water/cement ratio.
2. The reduction in water/cement ratio leads to an increase in strength of concrete.
3. Therefore, for a given workability an increase in the cement content results in an increase in strength of concrete.

Age of concrete:

The degree of hydration is synonymous with the age of concrete provided the concrete has not been allowed to dry out or the temperature is too low.

In theory, provided the concrete is not allowed to dry out, then it will always be increasing albeit at an ever reducing rate. For convenience and for most practical applications, it is generally accepted that the majority of the strength has been achieved by 28 days.

6.Compaction of concrete:


Any entrapped air resulting from inadequate compaction of the plastic concrete will lead to a reduction in strength. If there was 10% trapped air in the concrete, the strength will fall down in the range of 30 to 40%.

Temperature:

The rate of hydration reaction is temperature dependent. If the temperature increases the reaction also increases. This means that the concrete kept at higher temperature will gain strength more quickly than a similar concrete kept at a lower temperature.


However, the final strength of the concrete kept at the higher temperature will be lower. This is because the physical form of the hardened cement paste is less well structured and more porous when hydration proceeds at a faster rate.

This is an important point to remember because temperature has a similar but more pronounced detrimental effect on permeability of the concrete.



Relative humidity:

If the concrete is allowed to dry out, the hydration reaction will stop. The hydration reaction cannot proceed without moisture. The three curves show the strength development of similar concretes exposed to different conditions.



Curing:

It should be clear from what has been said above that the detrimental effects of storage of concrete in a dry environment can be reduced if the concrete is adequately cured to prevent excessive moisture loss.

5. Explain about hardened concrete properties (NOV 2019)

Theoretically, the introduction of aggregate of low permeability into cement paste, it is expected to reduce the permeability of the system because the aggregate particles intercept the channels of flows and make it take a circuitous route. Compared to neat cement paste, concrete with the same W/C ratio and degree of maturity, should give a lower coefficient of permeability. But in practice, it is seen from test data it is not the case. The introduction of aggregate, particularly larger size of aggregates increase the permeability considerably.

The explanation lies in the development of microcracks that are produced in the transition zone. Opinion differs in this regard about the size of microcracks that are generated at the transition zone. However, the drying shrinkage, thermal shrinkage and externally applied load may cause cracks in weak transition zone at the young age. It is reported that the size of the cracks in transition zone is much bigger than most of the capillary cavities present in cement paste

The use of pozzolanic materials in optimum proportion reduces the permeability of concrete. This is evidently due to the conversion of calcium hydroxide, otherwise soluble and leachable, into cementitious product.

Though air-entrainment, makes the concrete porous, when used up to 6%, makes the concrete more impervious, contrary to general belief.

Cement Content kg/m ³	Water/Cement Ratio	Permeability 10 ⁻¹² m/s
156	0.69	8
151	0.74	24
138	0.75	35
223	0.46	28

High pressure steam cured concrete in conjunction with crushed silica decreases the permeability. This is due to the formation of coarser C-S-H gel, lower drying shrinkage and accelerated conversion of Ca(OH)₂ into cementitious products.

Interaction Between Permeability, Volume Change and Cracking

In the preceding pages we have discussed about permeability, volume change and cracking of concrete are responsible for lack of durability of concrete and concrete structures. It is difficult to pin point which of these are primarily responsible for affecting durability. Permeability of concrete is often referred as the root cause for lack of durability. But it can be seen that volume change that takes place in an otherwise impervious concrete due to heat of hydration or internal manifestation can crack the concrete affecting durability. Microcracks in transition zone even in initially impermeable concrete, can start the cycle of deterioration process in concrete. Therefore, these three factors, one follows the

other two, like day follows the night, are responsible for affecting durability of concrete and concrete structures.

Acid Resistance (NOV 2019)

Cathodic Protection: Cathodic protection is one of the effective, well known, and extensively used methods for prevention of corrosion in concrete structures in more advanced countries. Due to high cost and long term monitoring required for this method, it is not very much used in India.

The cathodic protection comprises of application of impressed current to an electrode laid on the concrete above steel reinforcement. This electrode serves as anode and the steel reinforcement which is connected to the negative terminal of a DC source acts as a cathode. In this process the external anode is subjected to corrode and the cathodic reinforcement is protected against corrosion and hence the name “Cathodic protection”. In this process the negative chloride ions which are responsible for the damage of the passivating film, are drawn away from the vicinity of steel towards the anode where they are oxidised to form chlorine gas. The environment around the steel reinforcement reverts back to alkaline condition which protects the steel.


The other recent development in corrosion control methods are Realkalisation and Desalination.

The realkalisation process allows to make the concrete alkaline again and passivate the reinforcing steel by electrochemical method. This brings back the lost alkalinity of concrete to sufficiently high level to reform and maintain the passive layer on the steel.

In the desalination process the chloride ions are removed from the concrete, particularly from the vicinity of the steel reinforcement by certain electrical method to re-establish the passive layer on the steel.


6. Explain how you would determine the various elastic moduli for concrete (NOV 2017).

The modulus of elasticity can also be determined by subjecting a concrete beam to bending and then using the formulae for deflection and substituting other parameters. The modulus of elasticity so found out from actual loading is called static modulus of elasticity. It is seen that even under short term loading concrete does not behave as an elastic material. However, up to about 10-15% of the ultimate strength of concrete, the stress-strain graph is not very much curved and hence can give more accurate value. For higher stresses the stress-strain relationship will be greatly curved and as such it will be inaccurate. Figure shows stress-strain relationship for various concrete mixes.



In view of the peculiar and complex behaviour of stress-strain relationship, the modulus of elasticity of concrete is defined in somewhat arbitrary manner. The modulus of elasticity of concrete is designated in various ways and they have been illustrated on the stress-strain curve in Figure 8.2. The term Young's modulus of elasticity can strictly be applied only to the straight part of stress-strain curve. In the case of concrete, since no part of the graph is straight, the modulus of elasticity is found out with reference to the tangent drawn to the curve at the origin. The modulus found from this tangent is referred as initial tangent modulus. This gives satisfactory results only at low stress value. For higher stress value it gives a misleading picture.

Tangent can also be drawn at any other point on the stress-strain curve. The modulus of elasticity calculated with reference to this tangent is then called tangent modulus. The tangent modulus also does not give a realistic value of modulus of elasticity for the stress level much above or much below the point at which the tangent is drawn. The value of modulus of elasticity will be satisfactory only for stress level in the vicinity of the point considered.



A line can be drawn connecting a specified point on the stress-strain curve to the origin of the curve. If the modulus of elasticity is calculated with reference to the slope of this line, the modulus of elasticity is referred as secant modulus. If the modulus of elasticity is found out with reference to the chord drawn between two specified points on the stress-strain curve then such value of the modulus of elasticity is known as chord modulus.

The modulus of elasticity most commonly used in practice is secant modulus. There is no standard method of determining the secant modulus. Sometime it is measured at stresses ranging from 3 to 14 MPa and sometime the secant is drawn to point representing a stress level of 15, 25, 33, or 50 per cent of ultimate strength. Since the value of secant modulus decreases with increase in stress, the stress at which the secant modulus has been found out should always be stated.

Modulus of elasticity may be measured in tension, compression or shear. The modulus in tension is usually equal to the modulus in compression.

It is interesting to note that the stress-strain relationship of aggregate alone shows a fairly good straight line. Similarly, stress-strain relationship of cement paste alone also shows a fairly good straight line. But the stress-strain relationship of concrete which is combination of aggregate and paste together shows a curved relationship. Perhaps this is due to the development of micro cracks at the interface of the

aggregate and paste. Because of the failure of bond at the interface increases at a faster rate than that of the applied stress, the stress-strain curve continues to bend faster than increase of stress.

AMSCCE-1101

AMSCE - 1101